



XPass 2

Dispositivo RFID compacto para exteriores.



XP2-MDPB

XP2-GKDPB

XP2-GDPB

XPass 2 es un dispositivo compacto para exteriores basado en la tecnología RFID de última generación con plataforma de hardware múltiple de Suprema que proporciona una instalación perfecta en varios entornos.

XPass 2 también es compatible con la tecnología RFID de doble frecuencia (125 kHz / 13,56 MHz) y puede leer las frecuencias de los móviles mediante NFC y BLE. Su caja es resistente al agua y al polvo con



Características



Acceso móvil.

OSDP

Industry standard communication via OSD P.



Varias estructuras de hardw are.



Seguridad mejorada con Secure Element



IP67 - Resistente al agua y al polvo.



IK 08 - Resistente al vandalismo.



Lector de tarjetas múltiples



Alimentación a través de Ethernet

Especificaciones

125kHz card compatibility	EM
13.56MHz card compatibility	MIFARE, MIFARE Plus, DESFire EV1/EV2*, FeliCa
CPU	1.0GHz
Memory	4GB Flash + 64MB SDRAM
Max. Users	200,000
Max. Text Logs	1,000,000
Mobile card	NFC, BLE
IP rating	IP67
IK rating	IK08
Installation type	Mullion: XP2-MDPB Gangbox: XP2-GDPB, XP2-GKDPB
Keypad	Not Supported: XP2-MDPB, XP2-GDPB ...
Ethernet	Supported (10/100 Mbps, auto MDI/MDI-X)
RS-485	1ch Master or Slave
Wiegand	1ch In or Out
TTL	2ch Input
Relay	1 Relay
PoE	Supported (IEEE 802.3af compliant)
Sound	Multi-tone buzzer
Operating Temperature	-35 °C ~ 65 °C
Operating Humidity	0% ~ 95%, non-condensing
Power	DC 12V or DC 24V
Dimensions (WxHxD, mm)	48 x 145 x 27: XP2-MDPB 80 x 130 x 25: XP2-GDPB, XP2-GKDPB
Certificates	CE, FCC, KC, RoHS, REACH, WEEE, SIG

Configuración del sistema

